

MATERIAL DATA SHEET

NBR NITRILE / NYLON DIAPHRAGM SHEET RUBBER

CODE: TX1B1N4150. Nylon fabric 210 coated NBR black. Thickness 1.50mm		
ELASTOMER CHARACTERISTICS	VALUE	TEST METHOD
Elastomer	NBR Nitrile Rubber	
Hardness	70°(+/-5) Shore A	
Colour	Black	
FABRIC CHARACTERISTICS		
Fabric	PA 210 (235dTEX)	
Weight	110 (+/-5) g/m ²	
Thickness	0.20 (+/-0.01) mm	
COATED FABRIC CHARACTERISTICS		
Thickness	1.50mm (-0.00/+0.2)	UNI EN ISO 2286-3
Weight	1900 g/m ² (+/-10%)	UNI EN ISO 2286-2
Tensile Strength	Warp: Weft:	≥ 1100 N/5cm ≥ 1100 N/5cm
Elongation at Break	Warp: Weft:	≥ 20% ≥ 20%
Adhesion		≥ 20 N/cm
Temperature Range		-20°C to +100°C

Suitable for LPG, CNG, mineral oils, water.

Issue 1

1 August 2016

The above values are typical properties and are provided for information only. They should not be used to set specification Requirements. It is up to the end user to determine whether the material is suitable for the intended application.



J-FLEX

High Performance Elastomer Sheetings & Manufactured Components

Units 1 & 2, London Road Business Park, Retford,
Nottinghamshire, DN22 6HG, United Kingdom

tel: +44 (0) 1777 712 400 fax: +44 (0) 1777 712 409
www.j-flex.co.uk

