

# MATERIAL DATA SHEET

## THIN GAUGE SPECIFICATION NEOPRENE SHEET QUALITY: CR 496A

PROPERTY	VALUE	TEST METHOD
Colour	Black	
Hardness	60°(+/-5) Shore A	DIN 53505
Specific Weight	1.33(+/-0.02) g/cm <sup>3</sup>	DIN 53479
Tensile Strength	15.0 N/mm <sup>2</sup>	DIN 53504
Elongation	400%	DIN 53504
Temperature Resistance	-30° up to + 100° C	
Stock Thicknesses	0.5mm(+/-0.05) & 0.8mm(+/-0.1) ) (Smooth Surface Finish only)	
Chemical Resistance	Acid, Alkali, Oil, Grease UV, Ozone & Weather Resistant	

### Applications and Attributes

496 A is a specification grade of chloroprene rubber sheet that exhibits excellent abrasion resistance and very good flame and fuel resistance. 496 A can be used in gasket or diaphragm applications that are exposed to fuel or harsh weather conditions.

The performance of the sheeting when in contact with acids, alkalis and other chemicals may depend on the concentrations and temperatures involved. Suitability of the material for specific applications is subject to practical tests.

Issue ' 1

February 2020



### **J-FLEX** Innovative Rubber Solutions

Units 1 & 2, London Road Business Park, Retford,  
Nottinghamshire, DN22 6HG, United Kingdom

tel: +44 (0) 1777 712 400 fax: +44 (0) 1777 712 409

www. j-flex.com

