

FIRESLLEEVE



CERTIFICATE

ISO9001:2008, CE, EN 45545-2 (Fire and smoke toxicity testing), ROHS, MSDS

PRODUCT INTRODUCTION

Firesleeve is made of braided e-grade glass fiber sleeve with silicone rubber coating, which designed as a kind of heavy duty jacket to protect different kinds of hoses, wires and cables from the hazards of high heat and occasional flame. Good thermal insulation and fire proof performance make Firesleeve reduce heat energy losses and protect employees from burning effectively.

PRODUCT CHARACTERS

SIZE/INNER DIAMETER	4.5mm-150mm(1/5"-6")
COLOUR	Typically in iron oxide red and black,special colours accept customized.
WORKING TEMPERATURE	Continues working at 260°C,short time exposure to1650°C
RATE VOLTAGE	7kv--25kv
CHARACTER	High tempt. & flame resistant,insulation,anti-aging,avoiding splashing of the molten iron,abrasion resistant,water proof,oil proof,acid and alkali resistant.

STANDARD SPECIFICATIONS

Part No.	Inner Dia./mm	Inner Dia./inch	Wall Thickness/mm	Roll Length/mtr
HTSF06	06	1/4	1.5	20
HTSF08	08	5/16	1.6	20
HTSF10	10	3/8	1.8	20
HTSF13	13	1/2	1.9	20
HTSF15	15	5/8	2.1	20
HTSF20	20	3/4	2.4	20
HTSF22	22	7/8	2.5	20
HTSF25	25	1	2.6	20
HTSF30	30	1 1/8	2.9	20
HTSF32	32	1 1/4	3.0	20
HTSF35	35	1 3/8	3.1	20
HTSF38	38	1 1/2	3.2	20
HTSF40	40	1 5/8	3.4	20
HTSF45	45	1 3/4	3.4	20
HTSF50	50	2	3.6	20
HTSF55	55	2 1/4	3.7	20
HTSF60	60	2 3/8	3.8	20
HTSF65	65	2 1/2	3.8	20
HTSF70	70	2 3/4	4.0	20
HTSF75	75	3	4.1	20
HTSF80	80	3 1/8	4.3	15
HTSF85	85	3 1/4	4.3	15
HTSF90	90	3 1/2	4.5	15
HTSF95	95	3 3/4	4.5	15
HTSF100	100	4	4.6	15
HTSF105	105	4 1/8	4.7	10
HTSF110	110	4 3/8	4.7	10
HTSF115	115	4 1/2	4.7	10
HTSF120	120	4 3/4	4.8	10
HTSF125	125	5	4.8	10
HTSF130	130	5 1/8	5.0	10
HTSF140	140	5 1/2	5.2	10
HTSF150	150	6	5.2	10

APPLIED MODEL

