

## Thin Gauge Neoprene Sheet 60° Shore 'A'

PHYSICAL PROPERTY	RESULT	TEST METHOD
Polymer-Basis	Polychloropren-Rubber (CR)	
Colour	Black	
Hardness	60° ±5 Shore 'A'	DIN 53505
Specific Weight	1.35 ±0.02 g/cm <sup>3</sup>	DIN 53479
Tensile Strength (min)	15 N/mm <sup>2</sup>	DIN 53504
Elongation (min)	400%	DIN 53504
Temperature Resistance	-30°C up to +110°C	
Stock Thickness	0.5mm (±0.08)	
Stock Width	1200mm	

**Dimensional Tolerances:** are typically class 3 as standard, unless otherwise stated. Class 2 and Class 1 tolerances on request, in most instances.

**Disclaimer:** All recommendations and information contained in this specification sheet are to the best of our knowledge correct. Since conditions of service are beyond our control, users must satisfy themselves that the products are suitable for intended use. No warranty is given or implied in respect of information or recommendations or that any use of products will infringe rights belonging to other parties. In any event or occurrence our liability is limited to the invoice value of our goods delivered to you. We reserve the right to change product design and properties without notice.

**J-FLEX** Rubber Products



Certificate No. RS 27920

Units 1 & 2, London Road Business Park, Retford, Nottinghamshire, DN22 6HG, United Kingdom

tel: +44 (0) 1777 712400 fax: +44 (0) 1777 712409 email: sales@j-flex.com web: www.j-flex.com

